

Ultrasonic Bath (Sonicator) with Heater

Make: ANALAB | HSN Code: 84562000



Supplied with Lid, Basket, Power Cord, Operational & Instruction Manual with SOP, Calibration Test Certificate (Without Traceability Document) and Warranty Card.

Technical Specification:

Controller	: Microcontroller Based
Technology	: Latest IGBT Based
Display	: 6-digit Large LED Display for time & temperature
Timer	: 99 minutes and 59 seconds
Transducers	: PZT sandwich type, bonded at the base of SS tank.
Transducer Frequency	: 33 $\pm$ 3 KHz (40 KHz will be available optionally)
Frequency Display	: Yes
Temperature Range	: 5°C above ambient to 80°C
Type of Heater	: Silicon / Cartridge
Auto Degassing	: Yes, user adjustable time
Unit & Tank MOC	: Stainless Steel
Drain Valve	: ½" Ball Valve will be provided to clean the tank. (6.5 Liters & Above)
Power Supply	: 230VAC $\pm$ 10%, 50Hz

SR. No.	Model No.	Tank Capacity Liters	Tank Size (L X W X H)	Basket Size (L X W X H)	Ultrasonic Power Watts	Heater Power Watts
1	AU33-2.5 AU40-2.5	2.5	228 X 140 X 100 mm (9" X 5.5" X 4")	200 X 100 X 60 mm	60	240
2	AU33-3.5 AU40-3.5	3.5	300 X 150 X 100 mm (12" X 6" X 4")	250 X 100 X 60 mm	120	240
3	AU33-6.5 AU40-6.5	6.5	250 X 250 X 100 mm (10" X 10" X 4")	200 X 200 X 75 mm	180	240
4	AU33-10 AU40-10	10	300 X 228 X 150 mm (12" X 9" X 6")	270 X 190 X 100 mm	240	480
5	AU33-15 AU40-15	15	400 X 250 X 150 mm (16" X 10" X 6")	350 X 200 X 100 mm	360	480
6	AU33-20 AU40-20	20	455 X 300 X 150 mm (18" X 12" X 6")	420 X 270 X 100 mm	480	480
7	AU33-25 AU40-25	25	500 X 250 X 200 mm (20" X 10" X 8")	450 X 200 X 150 mm	600	480
8	AU33-30 AU40-30	30	500 X 300 X 200 mm (20" X 12" X 8")	450 X 250 X 150 mm	720	480
9	AU33-42 AU40-42	42	760 X 320 X 175 mm (30" X 13" X 7")	710 X 250 X 150 mm	780	720

Note:

1) Technical Specification like Size of Tank, Ultrasonic Power etc. may change without notice for purpose of continuous upgradation in instruments.

(Tank Capacity in Liter will remain unchanged OR better)

2) Price for Customized size will be available on request.

Product Range

•pH/mV/°C/ORP Analyzer •Conductivity/TDS/Resistivity/Salinity/°C Analyzer
•Multiparameter Analyzer (pH/ORP/Conductivity/TDS/Resistivity/Salinity/°C)
•Karl Fischer Titrator •Auto Titrator •Automatic Melting Point Apparatus
•Flame Photometer •Friability Test Apparatus •Tablet Dis-integration Test Apparatus
•Tap Density Test Apparatus •Tablet Hardness Tester •Leak Test Apparatus
•Tablet Dissolution Test Apparatus •Electromagnetic Sieve Shaker •Ultrasonic Bath (Sonicator) •Analytical Electronics Balance •Halogen Based Moisture Analyzer
•Visible & UV-Vis. Spectrophotometer •Nitrogen Gas Generator •Zero Air Gas Generator •Combination Nitrogen / Zero Air Gas Generator •Air Drying Unit for TOC Analyzer •Dew Point Apparatus •Gas Handling & Purification System •Laboratory Furniture & Fume Hood •Exhaust Hood for AAS/ICP.

ANALAB SCIENTIFIC INSTRUMENTS PVT. LTD.

AN ISO 9001 : 2015 CERTIFIED CO.
CIN: U33110GJ2005PTC046555



Plot No. 361, Sayajimarket,
N. H. No. 8 By-Pass,
At & Post : Sayajipura,
Vadodara - 390019, Gujarat, India.



+91 265 2514404, 9714503393



info@analab.co.in



www.analab.co.in, www.analabscientific.com

